



## DATA &amp; PARAMETER

	ACRONN DAZZLE PLUS 3.91 500x500mm
Pixel pitch (mm)	2.6
LED Type	SMD 3 IN 1 - SMD2121
Pixel m <sup>2</sup>	65536
Panel Dimension (mm)	500 (W) x 500 (H) x 75(D)
Panel Resolution WxH (pixels)	128 x 128
Manufacturing Material	Alluminium
Panel Weight (Kg)	9
Refresh Rate (Hz)	> 1920
Input power frequency	50 o 60 Hz
Brightness Control	256 level
Input Voltage	110 ~ 240 Volt
Viewing Angle VxH(Deg)	140 (+70/-70) / 140 (+70/-70)
Driver	MBI5124
Brightness (cd/ m2)	>1000
Power Cons. (W/m <sup>2</sup> ) Max	500
Power Cons. (W/m <sup>2</sup> ) AWG	200
Operating temperature (C°)	-20 to +50
Ambience humidity	10% to 90%
IP Protection	IP 43
Lifetime (50% Brightness)	100000 h
Blind spot rate	<1/10000
Control Distance	CAT5 cable: <100m; Single mode fiber:<10km
Signal input format	AV, S-Video, VGA, DVI, YpbPr, HDMI, SDI
Certifications	CE - EMC - RoHS

I dati tecnici sono soggetti a modifiche senza preavviso. Salvo errori ed omissioni. Versione: a partire da Luglio 2016