


[CATEGORIE](#)
[AZIENDA](#)
[NEWS & EVENTI](#)
[CONTATTI](#)
[DOVE SIAMO](#)
[VIDEO](#)
[Led display](#)

[Indoor](#)  
[Outdoor](#)  
[Rental](#)  
[Totem](#)

[Videoproiezione](#)

## LYX-SERIES

SMD P3.9-P4.8

[Torna a: Indoor Led Display](#)

[Richiedi informazioni](#)


### Specifiche tecniche

Model N.	LYX-P3.9	LYX-P4.8
Pixel Pitch	3.91mm	4.81mm
Pixel Configuration	1RG1B	1RG1B
LED Encapsulation	SMD2427	SMD3528
Resolution	65536/m <sup>2</sup>	43264/m <sup>2</sup>
Brightness	≥1300nit	≥1500nit
Color Temperature	6500-9500K	6500-9500K
Drive Mode	1/16	1/13
Cabinet Size	500*500*106mm	500*500*106mm
Cabinet Resolution	128*128	104*104
Cabinet Weight	≤9.5kg	≤9.5kg
Max Power Consumption	≤1200w/m <sup>2</sup>	≤1200w/m <sup>2</sup>
Average Power Consumption	≤600w/m <sup>2</sup>	≤600w/m <sup>2</sup>
Best Viewing angle	H:160° V:120°	H:140° V:120°
Refresh Rate	360-4800Mhz	360-4800Mhz
Grey Scale	14-16bit	14-16bit
Best View Distance	1.5--50m	4--50m
Protection Level	IP31	
Cabinet Material	Die-casting Aluminum	
Operating Voltage	220V/50Hz, 110V/60Hz	
Working Humidity	10% - 90%	
Working Temperature	-20--+50°	